LITEON
www.liteonit.com

16x8x8x /16x6x4x /16x/ + 48x24x48x DVD-Dual

Features

SHW-1635S

- ★ **ATAPI/E-IDE Half-Height internal DVD+R / DVD+RW / DVD-R / DVD-RW / DVD+R9/ DVD-R9/ DVD-ROM / CD-R/ CD-RW / CD-ROM combination drive**
- ★ **Support Double Layer DVD+/- R9 Recording Function**
- ★ **SMART-BURN(*1) avoiding Buffer Under Run error, Automatically adjusting writing strategy & running OPC to provide the best burning quality**
- ★ **SMART-X(*2) function adjusts CD-DA / VCD / DVD data extraction to a fastest allowable speed according to both data request rate from host and disk quality**
- ★ **VAS(*3) system reduce vibration and noise during recording and reading**
- ★ **Support Fixed Packet, Variable Packet, TAO, SAO, DAO, Raw Mode Burning & Over-Burn**
- ★ **DVD read compliant: DVD single/dual layer (PTP/OTP), DVD-R(3.9GB/4.7GB), DVD-R multi-borders, DVD+R, DVD+R multi-sessions, DVD-RW, and DVD+RW**
- ★ **CD read compliant: CD-DA, CD-ROM, CD-ROM/XA, Photo-CD, Multi-session, Karaoke-CD, Video-CD, CD-I FMV, CD Extra, CD Plus, CD-R, and CD-RW**
- ★ **Supprot both 8cm and 12cm disc of CD and DVD family**
- ★ **Conform to Orange Book: Part 2 CD-R Volume 1, Part 2 CD-R Volume 2 Multi Speed, Part 3 CD-RW Volume 1 (1x, 2x, and 4x), Part 3 CD-RW Volume2: High Speed, Part 3 CD-RW Volume 3: Ultra Speed**
- ★ **Supported transfer mode: PIO mode 4, DMA mode 2 and Ultra DMA mode 4**

Specifications

◎ **DVD Family :**

Write	
DVD+R	16X(21600KB/sec) maximum by CAV
DVD-R	16X(21600KB/sec) maximum by CAV
DVD+R9	8X(10800KB/sec) maximum by Zone CLV
DVD-R9	4X(5400KB/sec) maximum by CLV
ReWrite	
DVD+RW	8X(10800KB/sec) by CLV
DVD-RW	6X(8100KB/sec) by CLV
Read	16X(21600KB/sec) maximum by CAV
Access time	160ms

◎ **CD Family :**

Write	
CD-R	48X(7200KB/sec) maximum by CAV
ReWrite	
CD-RW	24X(3600KB/sec) maximum by Z-CLV in UltraSpeed disc
Read	48X(7200KB/sec) maximum by CAV
Access time	160ms

◎ **Buffer Size :** 2MB(MAX)

◎ **PC Required :** Pentium 4 1.3GHz or higherr CPU and 128MB or higher RAM are required
HDD must have access time < 20 ms; with a minimum of 650MB free space
9GB free space for creating a DVD image file (9GB for double layer; 5GB for single layer)

◎ **Compatibility :** Miscrosoft Windows 98SE/ME/2000/XP

◎ **MTBF(Life) :** 70000 POH

◎ **S/N Ration :** >75dB

◎ **Environment :**

Operating	5℃ to 50℃; Relative Humidity: 15% to 80%
Non-Operating	-40℃ to 65℃; Relative Humidity: 15% to 95%

◎ **Dimension :** 145(W) x 41.3(H) x 170(D) mm

◎ **Weight :** <0.9 Kg

◎ **Voltage Requirements :**
+5V +/-5% and less than 100 mVp-p ripple voltage
+12V +/-10% and less than 200 mVp-p ripple voltage

*1 **SMART-BURN : S**mart **M**onitoring & **A**dapting **R**ecording **T**echnology for **BURN**ing.
*2 **SMART-X : S**mart **M**onitoring & **A**djusting **R**ead-speed **T**echnology for e**X**traction.
*3 **VAS : V**ibration **A**bsorber **S**ystem

Copyright© LITE-ON IT Corp. All Rights Reserved. **Contents are subject to change without notice**